

Pure Water Storage Tank

Designed for pure water storage needs with minimal bacteria growth.

Minimize Bacteria Growth

- Cone bottom design for complete drainage
- Dual continuous internal spray down eliminates build-up of residual on tank walls
- Gasket sealed tank lid
- Dual check valves and air vent with 0.2-micron vent filter for protection from contaminants

Quality Features for a Clean Environment

- Polyethylene tank for minimal release of extractables
- Tank full shut off
- Pump protect low-level float

Robust Design for Longevity

- Plug and play interconnectivity to RO system makes installation a breeze
- Flow meter return stack includes return loop connection header, flow meter, sample port, pressure relief valve, pressure gauge, and thermometer
- ASAHI true union PVC 80 ball valves
- Stainless steel pressure gauges and temperature gauges
- All plumbing components are lead free, copper free and brass free



Cone bottom tank on poly base is compact with features to keep water maintained at the highest quality.

Model	Gallons	Dimensions With Stand & Fittings W x D x H	Inlet	Outlet	Return Loop	Vent Filter Cartridge Model
870010	55	36" x 31" x 65"	0.75"	1.5"	1"	134300
870110	100	36" x 31" x 92"	0.75"	1.5"	1"	134300
870210	250	50" x 45" x 92"	1"	1.5"	1"	134300
870310	325	50" x 45" x 110"	1"	1.5"	1"	134300
870215	250	56" x 45" x 92"	1"	1.5"	1.5"	134300
870315	325	56" x 45" x 110"	1"	1.5"	1.5"	134300
870500	500	68" x 56" x 104"	1"	2"	1.5"	132300