

# Multi-Cartridge Filter Vessel

*Multi-cartridge filter vessels provide economical filtration in a lightweight, externally polished stainless-steel design.*

## Designed for Ease of Use

- Swing bolt secured quick opening cover
- Internal positive pressure cartridge alignment and sealing plate
- Standard with EPDM seals
- Sample port on inlet and outlet for easy access

## Different Sizes Accommodate a Variety of Filters

- The vessel accommodates 20", 30" or 40" long cartridges
- Cartridges can be double open end (DOE) or 222 single open end (SOE)

## Corrosion Resistant

- Manufactured from polished and passivated stainless steel and rated for 150 PSI
- All cover bolt and leg mounting hardware is made from stainless steel



*Rust-free, stainless-steel housing is easy to use and lasts for years.*

Cartridge Filter Vessel Model	Gallons Per Minute	Dimensions H x W	Connections	Cartridge Size	# Cartridges	Absolute CMF Cartridge Model
880100	50	39.5" x 26"	1.5" PVC 80 SOC/FPT	2.5" x 20"	5	131700
880101	75	49" x 26"	2" PVC 80 SOC/FPT	2.5" x 30"	5	131500
880102	100	49" x 26"	2" PVC 80 SOC/FPT	2.5" x 40"	5	133100
880103	140	49" x 26"	2" PVC 80 SOC/FPT	2.5" x 40"	7	133100



**> 99.99% Bacteria  
Removal Final  
Filter**

### \*Certified Performance of Cartridge Filter

CMF Media	Certified to NSF/ANSI Std 42 & 61 by WQA Gold Seal Program	
All Other Materials	Conforms to NSF/ANSI Std 42	
Performance	Tested, Evaluated and Verified by the USEPA T & E Facility	
	MS2 Bacteriophage Virus	>99.9%
	Cryptosporidium	>99.999%
	RT Bacteria	>99.99%
	Legionella pneumophila	>99.9%
	Endotoxins**	96%
	**Independently tested	
Particle Removal	0.02 Micron	

Exchange Frequency: Exchange cartridge at 30 PSI differential pressure or after 6 months of use.